

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/113733 A1

(51) International Patent Classification⁷: **F04F 5/46, 5/44**

(21) International Application Number:
PCT/CH2003/000402

(22) International Filing Date: 20 June 2003 (20.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **DCI
DOUBLE-CONE TECHNOLOGY AG [CH/CH]**; All-
mendstrasse 86, CH-3602 Thun (CH).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **STARK, John**
[GB/CH]; Untere Zelg 3, CH-3665 Wattenwil (CH).

(74) Agent: **AMMANN PATENT ATTORNEYS LTD.**
BERNE; Schwarztorstrasse 31, CH-3001 Bern (CH).


(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DOUBLE CONE FOR GENERATION OF A PRESSURE DIFFERENCE



(57) Abstract: The present invention deals with a double-cone device that produces enhanced suction, pressure amplification and reduced noise. The enhancement is achieved by using a continuous geometry for the two frustoconical sections of the double-cone device. Further, a plurality of holes on the exit cone is used to suck the material into the device. Continuous geometry results in a stable flow profile that leads to reduced noise and enhanced amplification. Holes increase the suction force since they can be placed very close to the orifice. Further enhancements are also achieved by choosing the appropriate range of entry cone and exit cone angles.

BEST AVAILABLE COPY

WO 2004/113733 A1